

## SUPER SPORT LT500 SPECIFICATIONS

THE TRAILER YOUR CAR WOULD CHOOSE				
DECK LENGTH		5000 mm	DECK WIDTH	2000mm
OVERALL LENGTH		6500 mm	OVERALL WIDTH	2500 mm
FENDER HEIGHT		Fender on 235mm Fender off 195mm approx	GROUND CLEARANCE	385 mm
GVWR / GVM		2500 kg	GAWR (each axle)	1700 kg
TARE WEIGHT		600 kg	LOAD CAPACITY	1900 kg
DECK ANGLE		Only 3 degrees	FLARED TAIL WIDTH	2145 mm
ENGINEERED TO BE EFFORTLESS				
REMOVABLE FENDERS		Extruded aluminium, powder coated	LICENCE PLATE BRACKET	Aluminium, fold up
TIE POINTS		Continuous airline track & slotted chassis rail	WINCH	12V electric winch with wireless remote control
JACK		Centre mount jockey wheel, auto stow wheel	RIGGING	Double braided 12mm UHMWPE synthetic rope
WHEELS		165R13	COUPLING	50mm Snap-on steel coupler
AXLE (patented)		1700 kg galvanized steel torsion	TYRES	165R 13C 8 PLY Light Truck
HUBS		1700 kg	SUSPENSION	Independent torsion arm (PU)
BATTERY		12V 30AH Gel deep cycle	BRAKES	Electric
CHARGING		Onboard DC-DC to trailer plug aux pin & solar panel	ELECTRIC CONNECTOR	7-Way RV, flat pin trailer plug
LIGHTS				Micro LED fender mounted clearance Recessed LED stop, tail, indicators Combined LED/reflector marker lights
BUILT TO LAST A LIFETIME				
FINISH – ALUMINIUM PARTS Silver anodising & black powder coating			FINISH – STEEL PARTS Hot dip galvanized	
CHASSIS & TONGUE Extruded aluminium 6005-T6 Extruded 6005-T6 C section			DECK Extruded aluminium 6005-T6 interlocking panels	
OPTIONAL ACCESSORIES FOR SUPERSPORT				
SPARE WHEEL/TYRE KIT		TIE DOWN SET (PK4)	ROCK GUARD	
WINCH WITH WIRELESS REMOTE		LOCKABLE TYRE RACK	AIRLINE TRACK TIE DOWN RINGS	