

RAMP TRAILER RT500 SPECIFICATIONS

THE TRAILER YOUR CAR WOULD CHOOSE			
DECK LENGTH	5000 mm	DECK WIDTH	2000mm
OVERALL LENGTH	6500 mm	OVERALL WIDTH	2500 mm
FENDER HEIGHT	235mm	GROUND CLEARANCE	385 mm
GVWR / GVM	2500 kg	GAWR (each axle)	1700 kg
TARE WEIGHT	500 kg	LOAD CAPACITY	2000 kg
FLARED TAIL WIDTH	2145mm		
ENGINEERED TO BE EFFORTLESS			
LICENCE PLATE BRACKET	Aluminium, fold up	TIE POINTS	Continuous airline track & slotted chassis rail
COUPLING	50mm Snap-on steel coupler	JACK	Centre mount jockey wheel, auto stow wheel
TYRES	165R 13C 8 PLY Light Truck	WHEELS	13" Shiftr alloy
SUSPENSION	Independent torsion arm (PU)	AXLE	1700 kg galvanized steel torsion
BRAKES	10" electric brakes	HUBS	1700 kg
ELECTRIC CONNECTOR	7-Way RV, flat pin trailer plug	LIGHTS	Micro LED fender mounted clearance Recessed LED stop, tail, indicators Combined LED/reflector marker lights
BUILT TO LAST A LIFETIME			
FINISH – ALUMINIUM PARTS	Silver anodising & black powder coating	FINISH – STEEL PARTS	Hot dip galvanized
CHASSIS & TONGUE	Extruded aluminium 6005-T6	DECK	Extruded aluminium 6005-T6 interlocking panels